

Metric Steel Stud & Track

Drywall framing to EN 14195 and the metric stud and track range

Metric C-studs and matching U-tracks for plasterboard walls and ceilings, roll formed from galvanised coil. Stud width is chosen with the wall height, the plasterboard lining and the acoustic requirement.

Standard widths & data

Stud widths	51, 64, 76, 92 and 150 mm are the standard widths
Flange	35 mm typical for a standard stud
Base metal thickness (BMT)	0.50 – 1.5 mm
Lengths	2,700 mm and 4,800 mm are common stock lengths; cut to order
Ceiling sections	27 × 60 × 27 mm channel sections for suspended ceilings
Coating	Galvanised; pre-painted where specified

A stud is selected against the wall height and the load it carries — a non-load-bearing partition and a fire-rated or acoustic wall use different studs at the same width. Tell us the wall height, lining and fire/acoustic requirement.

Standards referenced

EN 14195:2014 (metal framing components for gypsum board systems — definitions, requirements and test methods) · EN 10346 (coated steel flat products) · AS/NZS 4600 (cold-formed steel structures — design, Australia / New Zealand) · AS 1397 (steel sheet and strip — hot-dip zinc-coated) · EN 1993-1-3 (cold-formed steel design, Europe)

Need a quote? Tell us the stud width, BMT, length and total metres.

zt-rfm.com · ztrollformmachine.com · +86 131 6656 7923 · steven@zt-rfm.com