

Suspended Ceiling Grid

Main tees, cross tees and wall angles for lay-in ceiling systems

Roll-formed galvanised grid for suspended lay-in ceilings: main runners, cross tees and wall angles. Members are cut with the standard end detail so sections engage at the intersections the module is laid to.

System layout

Module	600 × 600 mm and 600 × 1200 mm are the standard modules; 24 × 24 in. in imperial systems
Main runner spacing	1200 mm (4 ft) on centre, parallel to the panel length
Cross tee spacing	At the panel dimension — 600 mm or 1200 mm
Hanger wire	Minimum 12 gauge, at centres given by the installation standard
Member lengths	Cut to order (main tees commonly supplied in 3.6 m lengths)

Material & finish

Steel	Hot-dipped galvanised steel coil, roll formed
Finishes	Bare galvanised or pre-painted (standard white)
Load class	Light, intermediate and heavy duty classes per ASTM C635

Standards referenced

ASTM C635 (manufacture, performance and testing of the metal suspension system) · ASTM C636 (installation of metal ceiling suspension systems) · ASTM E580 (ceiling suspension systems for seismic areas, where applicable) · EN 13964 (EU suspended ceilings — product requirements)

Need a quote? Tell us the module, the grid type (exposed or concealed), finish, and total m².

zt-rfm.com · ztrollformmachine.com · +86 131 6656 7923 · steven@zt-rfm.com